



SPEC DATA SUBMITTAL SHEET



Piazza Stone® Piazza-Con Hex Washer Concrete Screws (Dagger- Guard Coating)

Size	TPI	Ctn Qty	Part Number	Drive	Thread	Drill Bit Size
3/16 x 1-1/4	16	100	PSCONH0316114	1/4"	Hi Low	5/32 x 3-1/2
3/16 x 1-3/4	16	100	PSCONH0316134	1/4"	Hi Low	5/32 x 3-1/2
1/4 x 1-1/4	14	100	PSCONH14114	5/16"	Hi Low	3/16 x 3-1/2
1/4 x 1-3/4	14	100	PSCONH14134	5/16"	Hi Low	3/16 x 3-1/2

Material:	C1022 LOW CARBON STEEL, CORE HARDNESS: HV240-425
Finish:	Dagger-Guard Coating is a three layer, multi step dip/spin bake process which provides 1000 hour salt spray corrosion resistance
Application:	Piazza clips to lightweight stone masonry units
Installation:	Pre-drill hole with masonry drill bit. Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM into pre-drilled hole. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is full seated when the head's bearing surface is flush with the material being attached.

Meets or exceeds the following specifications:

ASTM A510	Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel (Minimum grade 1018)
ASTM B117	Practice for Operating Salt Spray (Fog) Apparatus

See attached test reports

These figures are offered only as a guide and are not guaranteed in any way by Piazza Stone, LLC. Appropriate safety factors should be applied to these values for specific purposes.