



### **Suggested Water Sealant: PWS-5 Regular Strength**

Professional® Water Sealant – PWS-5 Water Sealant unmatched waterproofing protection on concrete, brick, block, precast, pavers, manufactured stone, natural stone, ArcusStone, stucco, marble, slate, treated wood, landscaping stone, exposed aggregate, clay brick, saltillo tile, travertine, granite, marble, stained concrete, colored concrete, natural stone and other porous materials. This clear, penetrating, RTV Silicone sealer is a proprietary blend of inorganic silicone polymers which provide maximum resistance to breakdown from the sun's damaging UV light, as well as resistance to acid rain. PWS-5 Water Sealant's unique silicone technology allows it to remain flexible inside the substrate to allow for bridging of hairline cracks and protect against building freeze-thaw cycles. PWS-5 Water Repellent remains breathable to allow moisture vapor to escape while preventing outside water penetration. Provides a durable, long-lasting natural look finish once applied and does not change the appearance. Simple 1-coat application, 5-Year and 10-Year warranties available. Meets ASTM E-514 Water Repellency and 98-mph Wind Driven Rain Conditions.

- Clear Liquefied RTV Silicone Rubber Sealant
- Cures in 1 hour
- Vertical or Horizontal applications
- Cost Effective, Long Lasting
- Easy to apply with low-pressure pump-up sprayer
- Can be brushed on small hard to reach areas
- One Coat Formula
- Bridges hairline cracks
- Breathable — allows moisture vapor to escape while preventing water penetration
- Penetrating
- Does not change surfaces color
- Durable & long lasting — not affected by UV rays, airborne pollutants, salt spray, or acid rain
- Meets ASTM E-514 Water Repellency and 98-mph Wind Driven Rain Conditions
- For Exterior Use Only

### **Application:**

*Do not apply until piece has cured for 30 days.*

If crack is visible at 6', patch with Piazza Patch, then apply PWS-5 to bridge the crack.

If crack is not visible at 6', apply PWS-5 sealant to bridge the crack.

Apply PWS-5 only on the complete surface where the crack is exposed. (to all four corners of surface)

Manufacturer: Professional Products of Kansas, Inc

Phone: 1-800-676-7346